


# **Specifications**



## **Unit Design Conditions and Capacities**

32000
24000-36000
4800
5280
26720
14400
977.0
781.6
481.6
364.8
NG-064
1000
3"
90/8
2
585

## \*Capacities at 82F/60%RH.

Voltage	208-240/03	460-480/03	575-600/03
MCA	370	180	145
MOP	450	225	175

#### Standard Features

- CommandCenter microprocessor
- WebSentry internet monitoring (1 yr free labor warranty when connected)
- Protocol design
- Direct drive plenum fans
- Fully dipped coils
- Multiple supply orientations
- 2" Double walled cabinet
- 2 Year parts warranty

#### **Optional Features Shown**

- Heat recovery on minimum exhaust/outside air
- Purge/Economizer
- Hot water auxiliary heating coil
- Pool water heating

### **Available Options**

- BACnet IP, Modbus or LonWorks interface
- Indoor or outdoor cabinet design
- Outdoor packaged available
- Heat rejection to cooling tower or geo-loop
- Gas, electric ,or hot water auxiliary heating
- Remote CommandCenter panel
- Motorized OA damper with occupied schedule
- Mirrored cabinet
- Higher or lower supply airflows or static pressures
- Higher or lower OA/EA airflows
- Unit mounted disconnect
- Extended warranties